The ANY-maze Cue lights



Overview

The ANY-maze cue lights are perfect for presenting visual cues to animals during behavioural tests. Available in three sizes (22mm, 14mm and 10mm) and five colours (red, green, yellow, blue and white), these LED lights are water resistant and easy to mount into panels up to 6.3mm (1/4 inch) thick. Their 2 metre (6 foot) leads connect directly to the ANY-maze Digital interface.

22mm Cue lights

- Available in colours of Red, Green, Yellow, Blue and White.
- Water resistant.
- Mount in panels up to 7.6mm thick.
- 2 metre cable.

14mm Cue lights

- Available in colours of Red, Green, Yellow, Blue and White.
- Water resistant.
- Mount in panels up to 6.3mm thick.
- 2 metre cable.

10mm Cue lights

- Available in colours of Red, Green and Yellow.
- Water resistant.
- Mount in panels up to 8mm thick.
- 2 metre cable.

Part numbers

60045R	22mm	Red
60045G	22mm	Green
60045Y	22mm	Yellow
60045B	22mm	Blue
60045W	22mm	White
60046R	14mm	Red
60046G	14mm	Green
60046Y	14mm	Yellow
60046B	14mm	Blue
60046W	14mm	White
60047R	10mm	Red
60047G	10mm	Green
60047Y	10mm	Yellow

Mechanical specification

22mm Cue light		
Colours	Red, Green, Yellow, Blue, White	
Mounting hole	22mm (0.866")	
Maximum panel thickness	7.6mm (0.30")	
Minimum spacing	40mm (1.58") centre to centre	
Cable length	200cm (6' 7")	
	¢ 1.01 in[25.6mm]	
14mm Cue light		
Colours	Red, Green, Yellow, Blue, White	
Mounting hole	14.0mm (0.551")	
Maximum panel thickness	6.3mm (0.250")	
Minimum spacing Cable length	27mm (1.05") centre to centre 200cm (6' 7")	
() () () () () () () () () () () () () (Ø.67in [17mm]	
10mm Cue light		
Colours	Red, Green, Yellow	
Mounting hole 10.1mm (0.4")		
Maximum panel thickness 8.1mm (0.31")		
Minimum spacing	17mm (0.67") centre to centre	
Cable length	200cm (6' 7")	
BLACK WIRE CATHODE (-)	NUT WASHER MOISTURE-SEAL FRESNEL LENS & LED (WITHIN) Ø.500 [12.7mm]	